

```

        "--show",
        "-s",
        action="store_true",
        help=("Show which files would be removed but don't remove them"),
    )

```

Add a Boolean --show flag to the command.

To determine which files should be removed, you need to create a set containing all the files associated with `Musician` and `Venue` objects and find the difference between that and the files on disk. The following listing finds the orphaned file set.

Listing E.41 Determining which files should be removed

```

# RiffMates/bands/management/commands/cleanup.py
...

class Command(BaseCommand):
    ...
    def handle(self, *args, **options):
        model_set = set()
        for musician in Musician.objects.all():
            if musician.picture:
                model_set.add(Path(musician.picture.path))
        for venue in Venue.objects.all():
            if venue.picture:
                model_set.add(Path(venue.picture.path))

        file_set = set(settings.MEDIA_ROOT.glob("**/*"))

        orphaned = file_set.difference(model_set)

```

Store the files used by models as a set.

Iterate over all Musician objects, and add each bio-pic to the set.

Iterate over all Venue objects, and add each picture to the set.

Find all the files on the hard drive.

The difference between the `model_set` and `file_set` subtracts all of the model and venue files from the whole list, leaving just those that are orphaned.

Once the set of orphans is determined, you can perform the removal action on it. The following listing conservatively comments out the actual deletion. Only uncomment the `path.unlink()` line if you're sure your code works.

Listing E.42 Determining which files should be removed

```

# RiffMates/bands/management/commands/cleanup.py
...

class Command(BaseCommand):
    ...
    def handle(self, *args, **options):
        ...
        if not orphaned:
            self.stdout.write("No orphaned files")
            exit()

        if options["show"]:

```

If the set of orphans is empty, inform the user there is nothing to delete.

If the --show flag is present, only display the orphaned files—don't delete them.