

Listing E.54 Modifying the parent template, so the nav bar can be overloaded

```

<!-- RiffMates/templates/base.html -->
<!-- ... -->
<body>
  {% block nav %}
    <div style="float: right;">
      <a href="{% url 'home' %}">Home</a> &nbsp;&nbsp;&nbsp;
    <!-- ... -->
  </div>
  {% endblock nav %}
<!-- ... -->

```

Wrapping the nav in a `{% block %}` tag for later.

The current `<div>` for the nav

With the newly wrapped nav, the content for the tabbed page can override it, so it only gets displayed once. The following listing shows the HTML, which includes the `hx-get` attributes for fetching each tab's contents.

Listing E.55 HTML for the tabbed page

```

<!-- RiffMates/templates/tabbed_listing.html -->
{% extends "base.html" %}

{% block nav %}
  # empty block to ensure you don't get the nav twice #
{% endblock %}

{% block content %}
  <div>
    <a
      hx-get="/bands/musicians/"
      hx-target="#tab-block"
      hx-swap="innerHTML"
      style="cursor: pointer; text-decoration: underline;"
    >Musicians</a>
    &nbsp;&nbsp;&nbsp;

    <a
      hx-get="/bands/venues/"
      hx-target="#tab-block"
      hx-swap="innerHTML"
      style="cursor: pointer; text-decoration: underline;"
    >Venues</a>

  </div>

  <div id="tab-block">
    <div
      hx-get="/bands/musicians/"
      hx-trigger="load"
      hx-swap="outerHTML"/>

    </div>
  </div>
{% endblock content %}

```

Override the nav block, rendering it as empty; the page's nav will be displayed by the included content page.

A container for the tabbed interface

Each tab is a link with the `hx-get` fetching the content from an existing view.

The target tag to replace with fetched content

Only replace the contents inside the target tag.

The lack of an `href` attribute means the browser needs extra styling information.

The container for the displayed contents

The default tab on page load is the first one—fetch it.

Trigger the default tab as soon as the page is loaded.