

that URL subpath against your view, you pass a reference to the `credits` function to the `path` object. Remember, as it is a reference to a function, you aren't calling it, and don't use parentheses—it is `credits`, not `credits()`.

In this code, I import the module and use a dotted reference to the view: `home_views.credits`. Instead, you could import the view from the module, but as you add more views to `home/views.py`, that would require a lot of importing.

Other ways of specifying paths

Older versions of Django provided a different mechanism for specifying the structure of a URL to register against that looked like a regular expression. Some programmers still prefer the power of regular expressions when registering routes, so `re_path` exists if you prefer that style or have a particularly fancy route not covered by `path`. I recommend switching to the newer style, as it is generally easier to read and use. For more information on `re_path`, see <http://mng.bz/wxy5>.

2.7 Visiting your view

You're almost ready to go. The last time you ran the development server, you got a warning message: 18 unapplied migrations. Django tracks when you make changes to database models and creates special scripts, called *migrations*, for making database changes. The unapplied migrations are scripts for built-in apps, like the Django Admin. In later chapters, you'll write your own database objects, but for now, you can run a migration to get rid of the warning.

The management command to run database migrations is `migrate`. Before running the development server, run `python manage.py migrate` to remove the unapplied migrations warning:

```
(venv) RiffMates$ python manage.py migrate
```

Running `migrate` produces a lot of output; you will see a list of the apps that required migration (Apply all migrations: `admin`, `auth`, `contenttypes`, `sessions`), along with the output from each migration app. The output will include the full name of the app and migration script. For example, `Applying admin.0001_initial...` OK indicates the script `0001_initial` for the `admin` app was run successfully.

The `migrate` command applies migration scripts across several modules. You'll learn all about this in detail in a future chapter.

Restart the development server. This time, you won't get the warning:

```
(venv) RiffMates$ python manage.py runserver
Watching for file changes with StatReloader
Performing system checks...

System check identified no issues (0 silenced).

Django version 5.0.2, using settings 'RiffMates.settings'
Starting development server at http://127.0.0.1:8000/
Quit the server with CONTROL-C.
```