

used `os.join()` and strings to specify a path, so be careful if you are dealing with older code. Modify the `DIRS` option of the `TEMPLATES` configuration in `settings.py` to point your newly created `RiffMates/templates` directory. The resulting configuration for `TEMPLATES` is shown in the following listing.

Listing 3.8 Change your settings to point at the new templates directory

```
# RiffMates/RiffMates/settings.py
...
TEMPLATES = [
    {
        'BACKEND': 'django.template.backends.django.DjangoTemplates',
        'DIRS': [ BASE_DIR / 'templates', ],
        'APP_DIRS': True,
        'OPTIONS': {
            'context_processors': [
                'django.template.context_processors.debug',
                'django.template.context_processors.request',
                'django.contrib.auth.context_processors.auth',
                'django.contrib.messages.context_processors.messages',
            ],
        },
    ],
]
```

Add your templates directory to the list of directories where Django looks for templates.

If APP_DIRS is used at the same time as DIRS, the app directories will be searched after the DIRS directories.

Your view is in place, and you have told Django where to look for `news.html`. The only thing left is to create `news.html`. This template is relatively small, containing a header and a `{% for %}` loop inside a `<ul>` tag. The `{% for %}` loop iterates over the `newslist` in the context dictionary and creates an `<li>` item for each list entry. Create `RiffMates/templates/news.html` according to the following listing.

Listing 3.9 HTML template to be rendered by the news view

```
<!-- RiffMates/templates/news.html -->
<!doctype html>
<html lang="en">
<head>
    <title>RiffMates News</title>
</head>
<body>
    <h1>RiffMates News</h1>

    <ul>
        {% for item in news %}
            <li>{{ item }}</li>
        {% endfor %}
    </ul>
</body>
</html>
```