

```
<body>
  {% block content %}
  {% endblock content %}
</body>
</html>
```

The closing `{% endblock %}` can optionally include the same name as its corresponding `{% block %}` tag. If you don't specify the name, the most recent block gets closed. By including the name of the block in the closing tag, you make your code clearer in the case of nested blocks.

To use your new `base.html`, you create a child page containing the `{% extends %}` tag. This tag takes a single argument: the name of the template it is extending. Inside the child file, you override the blocks declared in the parent and insert the corresponding content. Create `news2.html`, a new version of the News page. This file declares two blocks: one to override the title and the other to override the content.

Inside a block, there is a handy context variable named `{{ block.super }}`. This variable contains the content of the parent block. This is useful if you want to add to the parent block rather than completely replace it. Inside `news2.html` write content similar to that in the following listing.

Listing 3.16 A new 'News' file

```
<!-- RiffMates/templates/news2.html -->
{% extends "base.html" %}

{% block title %}
  {{block.super}}: News
{% endblock %}

{% block content %}
  <h1>RiffMates News (2)</h1>

  <ul>
    {% for item in news %}
      <li>{{ item }}</li>
    {% endfor %}
  </ul>

{% endblock content %}
```

Because you added a new template file instead of modifying the existing one, you need to update your `news()` view. Edit `RiffMates/home/views.py` and change the `render()` call to point to the newly created `news2.html` file.

Once you have done that, run the development server and visit `http://localhost:8000/news/` again to see the change. The page will be similar to before but this time with the 2 tacked onto the `<h1>` tag to prove it worked. Although the result in the browser is the same, `news2.html` is shorter than `news.html`, and if you start styling to your base page, it will be applied across every template that inherits from `base.html`.