

```

        # Any disk can be moved onto an empty "to" tower:
        return fromTower, toTower
    elif towers[toTower][-1] < towers[fromTower][-1]:
        print("Can't put larger disks on top of smaller ones.")
        continue # Ask player again for their move.
    else:
        # This is a valid move, so return the selected towers:
        return fromTower, toTower

```

This function is 34 lines long. Although it covers multiple tasks, including allowing the player to enter a move, checking whether this move is valid, and asking the player again to enter a move if the move is invalid, these tasks all fall under the umbrella of getting the player's move. On the other hand, if we were devoted to writing short functions, we could break the code in `getPlayerMove()` into smaller functions, like this:

```

def getPlayerMove(towers):
    """Asks the player for a move. Returns (fromTower, toTower)."""

    while True: # Keep asking player until they enter a valid move.
        response = askForPlayerMove()
        terminateIfResponseIsQuit(response)
        if not isValidTowerLetters(response):
            continue # Ask player again for their move.

    # Use more descriptive variable names:
    fromTower, toTower = response[0], response[1]

    if towerWithNoDisksSelected(towers, fromTower):
        continue # Ask player again for their move.
    elif len(towers[toTower]) == 0:
        # Any disk can be moved onto an empty "to" tower:
        return fromTower, toTower
    elif largerDiskIsOnSmallerDisk(towers, fromTower, toTower):
        continue # Ask player again for their move.
    else:
        # This is a valid move, so return the selected towers:
        return fromTower, toTower

def askForPlayerMove():
    """Prompt the player, and return which towers they select."""
    print('Enter the letters of "from" and "to" towers, or QUIT.')
    print("(e.g. AB to moves a disk from tower A to tower B.)")

```