

```

print()
return input("> ").upper().strip()

def terminateIfResponseIsQuit(response):
    """Terminate the program if response is 'QUIT'"""
    if response == "QUIT":
        print("Thanks for playing!")
        sys.exit()

def isValidTowerLetters(towerLetters):
    """Return True if `towerLetters` is valid."""
    if towerLetters not in ("AB", "AC", "BA", "BC", "CA", "CB"):
        print("Enter one of AB, AC, BA, BC, CA, or CB.")
        return False
    return True

def towerWithNoDisksSelected(towers, selectedTower):
    """Return True if `selectedTower` has no disks."""
    if len(towers[selectedTower]) == 0:
        print("You selected a tower with no disks.")
        return True
    return False

def largerDiskIsOnSmallerDisk(towers, fromTower, toTower):
    """Return True if a larger disk would move on a smaller disk."""
    if towers[toTower][-1] < towers[fromTower][-1]:
        print("Can't put larger disks on top of smaller ones.")
        return True
    return False

```

These six functions are 56 lines long, nearly double the line count of the original code, but they do the same tasks. Although each function is easier to understand than the original `getPlayerMove()` function, the group of them together represents an increase in complexity. Readers of your code might have trouble understanding how they all fit together. The `getPlayerMove()` function is the only one called by other parts of the program; the other five functions are called only once, from `getPlayerMove()`. But the mass of functions doesn't convey this fact.

I also had to come up with new names and docstrings (the triple-quoted strings under each `def` statement, further explained in Chapter 11) for each new function. This leads to functions with confusingly similar names, such as `getPlayerMove()` and `askForPlayerMove()`. Also, `getPlayerMove()` is still longer