
All the files in the *wizcoin* folder are currently untracked ❶. We can track them by doing an initial commit of these files, which takes two steps: running `git add` for each file to be committed, and then running `git commit` to create a commit of all these files. Once you've committed a file, Git tracks it.

The `git add` command moves files from the untracked state or modified state to the staged state. We could run `git add` for every file we plan to stage (for example, `git add .coveragerc`, `git add .gitignore`, `git add LICENSE.txt`, and so on), but that's tedious. Instead, let's use the `*` wildcard to add several files at once. For example, `git add *.py` adds all *.py* files in the current working directory and its subdirectories. To add every untracked file, use a single period (`.`) to tell Git to match all files:

```
C:\Users\Al\wizcoin>git add .
```

Run `git status` to see the files you've staged:

```
C:\Users\Al\wizcoin>git status
On branch master
```

```
No commits yet
```

❶ Changes to be committed:
(use "`git rm --cached <file>...`" to unstage)

```
    ❷ new file:   .coveragerc
      new file:   .gitignore
--snip--
      new file:   tox.ini
```

The output of `git status` tells you which files are staged to be committed the next time you run `git commit` ❶. It also tells you that these are new files added to the repo ❷ rather than existing files in the repo that have been modified.

After running `git add` to select the files to add to the repo, run `git commit -m "Adding new files to the repo."` (or a similar commit message) and `git status` again to view the repo status: