

```
+ >>> str(coin)
+ '2g, 5s, 10k'
+ >>> coin.value()
+ 1141
```

Contribute

The output shows that *README.md* in your working copy has changed from the *README.md* as it exists in the latest commit of the repo. The lines that begin with a minus sign - have been removed; the lines that begin with a plus sign + have been added.

While reviewing the changes, you'll also notice that we made a typo by writing `xample` instead of `example`. We shouldn't check in this typo. Let's correct it. Then run `git diff` again to inspect the change and add and commit it to the repo:

```
C:\Users\Al\wizcoin>git diff
diff --git a/README.md b/README.md
index 76b5814..3be49c3 100644
--- a/README.md
+++ b/README.md
@@ -13,7 +13,14 @@ To install with pip, run:
 Quickstart Guide
-----

-TODO - fill this in later
+Here's some example code demonstrating how this module is used:
--snip--
C:\Users\Al\wizcoin>git add README.md

C:\Users\Al\wizcoin>git commit -m "Added example code to README.md"
[master 2a4c5b8] Added example code to README.md
1 file changed, 8 insertions(+), 1 deletion(-)
```

The correction is now safely committed to the repo.

Using git difftool to View Changes with a GUI Application

It's easier to see changes with a diff program that uses a GUI. On Windows, you can download WinMerge (<https://winmerge.org/>), a free, open source