

Additionally, run `git config --global difftool.prompt false` so Git doesn't ask for confirmation each time you want to open the diff tool. If you installed a GUI Git client, you can also configure it to use these tools (or it might come with a visual diff tool of its own).

How Often Should I Commit Changes?

Even though version control allows you to roll back your files to an earlier commit, you might wonder how often you should make commits. If you commit too frequently, you'll have trouble sorting through a large number of insignificant commits to find the version of the code you're looking for. If you commit too infrequently, each commit will contain a large number of changes, and reverting to a particular commit will undo more changes than you want to. In general, programmers tend to commit less frequently than they should.

You should commit code when you've completed an entire piece of functionality, such as a feature, class, or bug fix. Don't commit any code that contains syntax errors or is obviously broken. Commits can consist of a few lines of changed code or several hundred, but either way, you should be able to jump back to any earlier commit and still have a working program. You should always run any unit tests before committing. Ideally, all your tests should pass (and if they don't pass, mention this in the commit message).

Deleting Files from the Repo

If you no longer need Git to track a file, you can't simply delete the file from the filesystem. You must delete it through Git using the `git rm` command, which also tells Git to untrack the file. To practice doing so, run the `echo "Test file" > deleteme.txt` command to create a small file named *deleteme.txt* with the contents "Test file". Then commit it to the repo by running the following commands:

```
C:\Users\Al\wizcoin>echo "Test file" > deleteme.txt
C:\Users\Al\wizcoin>git add deleteme.txt
C:\Users\Al\wizcoin>git commit -m "Adding a file to test Git deletion."
[master 441556a] Adding a file to test Git deletion.
 1 file changed, 1 insertion(+)
```