

```
C:\Users\Al\wizcoin>git commit -m "Testing the moving of files in Git."
[master 3ed22ed] Testing the moving of files in Git.
1 file changed, 0 insertions(+), 0 deletions(-)
rename README.txt => movetest/README.txt (100%)
```

You can also rename and move a file at the same time by passing `git mv` a new name and location. Let's move the *README.txt* back to its original place at the root of the working directory and give it its original name:

```
C:\Users\Al\wizcoin>git mv movetest/README.txt README.md
C:\Users\Al\wizcoin>git status
On branch master
Changes to be committed:
  (use "git reset HEAD <file>..." to unstage)

        renamed:    movetest/README.txt -> README.md
```

```
C:\Users\Al\wizcoin>git commit -m "Moving the README file back to its original
place and name."
[master 962a8ba] Moving the README file back to its original place and name.
1 file changed, 0 insertions(+), 0 deletions(-)
rename movetest/README.txt => README.md (100%)
```

Note that even though the *README.md* file is back in its original folder and has its original name, the Git repo remembers the moves and name changes. You can see this history using the `git log` command, described in the next section.

Viewing the Commit Log

The `git log` command outputs a list of all commits:

```
C:\Users\Al\wizcoin>git log
commit 962a8baa29e452c74d40075d92b00897b02668fb (HEAD -> master)
Author: Al Sweigart <al@inventwithpython.com>
Date:   Wed Sep 1 10:38:23 2021 -0700

    Moving the README file back to its original place and name.

commit 3ed22ed7ae26220bbd4c4f6bc52f4700dbb7c1f1
Author: Al Sweigart <al@inventwithpython.com>
```