

Date: Wed Sep 1 10:36:29 2021 -0700

Testing the moving of files in Git.

--snip--

---

This command can display a large amount of text. If the log won't fit in your Terminal window, it'll let you scroll up or down using the up and down arrow keys. To quit, press the **q** key.

If you want to set your files to a commit that's earlier than the latest one, you need to first find the *commit hash*, a 40-character string of hexadecimal digits (composed of numbers and the letters A to F), which works as a unique identifier for a commit. For example, the full hash for the most recent commit in our repo is 962a8baa29e452c74d40075d92b00897b02668fb. But it's common to use only the first seven digits: 962a8ba.

Over time, the log can get very lengthy. The `--oneline` option trims the output to abbreviated commit hashes and the first line of each commit message. Enter `git log --oneline` into the command line:

---

```
C:\Users\Al\wizcoin>git log --oneline
962a8ba (HEAD -> master) Moving the README file back to its original place and
name.
3ed22ed Testing the moving of files in Git.
15734e5 Deleting deleteme.txt from the repo to finish the deletion test.
441556a Adding a file to test Git deletion.
2a4c5b8 Added example code to README.md
e1ae3a3 An initial add of the project files.
```

---

If this log is still too long, you can use `-n` to limit the output to the most recent commits. Try entering `git log --oneline -n 3` to view only the last three commits:

---

```
C:\Users\Al\wizcoin>git log --oneline -n 3
962a8ba (HEAD -> master) Moving the README file back to its original place and
name.
3ed22ed Testing the moving of files in Git.
15734e5 Deleting deleteme.txt from the repo to finish the deletion test.
```

---