

```
df617da Renaming bacon() to cheese().
ef1e4bb Refactoring bacon().
ac27c9e Adding bacon() function.
009b7c0 Adding better documentation to spam().
0657588 Creating spam() function.
d811971 Initial add.
```

---

But I've decided I want to revert the file back to before I added `bacon()` without changing any other files in the repo. I can use the `git show <hash>:<filename>` command to display this file as it was after a specific commit. The command would look something like this:

---

```
C:\Users\Al\myproject>git show 009b7c0:eggs.py
<contents of eggs.py as it was at the 009b7c0 commit>
```

---

Using the `git checkout <hash> -- <filename>`, I could set the contents of `eggs.py` to this version and commit the changed file as normal. The `git checkout` command only changes the working copy. You'll still need to stage and commit these changes like any other change:

---

```
C:\Users\Al\myproject>git checkout 009b7c0 -- eggs.py

C:\Users\Al\myproject>git add eggs.py

C:\Users\Al\myproject>git commit -m "Rolled back eggs.py to 009b7c0"
[master d41e595] Rolled back eggs.py to 009b7c0
 1 file changed, 47 deletions(-)

C:\Users\Al\myproject>git log --oneline
d41e595 (HEAD -> master) Rolled back eggs.py to 009b7c0
895d220 Adding email support to cheese().
df617da Renaming bacon() to cheese().
ef1e4bb Refactoring bacon().
ac27c9e Adding bacon() function.
009b7c0 Adding better documentation to spam().
0657588 Creating spam() function.
d811971 Initial add.
```

---

The `eggs.py` file has been rolled back, and the rest of the repo remains the same.