
```
C:\Users\Al>git clone https://github.com/<github_username>/wizcoin.git
Cloning into 'wizcoin'...
remote: Enumerating objects: 5, done.
remote: Counting objects: 100% (5/5), done.
remote: Compressing objects: 100% (3/3), done.
remote: Total 5 (delta 0), reused 5 (delta 0), pack-reused 0
Unpacking objects: 100% (5/5), done.
```

You can now commit and push changes using this Git repo just as you would if you had run `git init` to create the repo.

The `git clone` command is also useful in case your local repo gets into a state that you don't know how to undo. Although it's less than ideal, you can always save a copy of the files in your working directory, delete the local repo, and use `git clone` to re-create the repo. This scenario happens so often, even to experienced software developers, that it's the basis of the joke at <https://xkcd.com/1597/>.

Summary

Version control systems are lifesavers for programmers. Committing snapshots of your code makes it easy to review your progress and, in certain cases, roll back changes you don't need. Learning the basics of a version control system like Git certainly saves you time in the long run.

Python projects typically have several standard files and folders, and the `cookiecutter` module helps you create the starting boilerplate for many of these files. These files make up the first files you commit to your local Git repo. We call the folder containing all of this content the *working directory* or *project folder*.

Git tracks the files in your working directory, all of which can exist in one of three states: committed (also called unmodified or clean), modified, or staged. The Git command line tool has several commands, such as `git status` or `git log`, that let you view this information, but you can also install several third-party GUI Git tools.

The `git init` command creates a new, empty repo on your local computer. The `git clone` command copies a repo from a remote server, such as the popular GitHub website. Either way, once you have a repo, you can use `git`