

```
print('Total value:', purse.value())
print('Weight:', purse.weightInGrams(), 'grams')

print()
```

```
❷ coinJar = wizcoin.WizCoin(13, 0, 0) # The ints are passed to __init__().
print(coinJar)
print('G:', coinJar.galleons, 'S:', coinJar.sickles, 'K:', coinJar.knuts)
print('Total value:', coinJar.value())
print('Weight:', coinJar.weightInGrams(), 'grams')
```

---

The calls to `WizCoin()` ❶ ❷ create a `WizCoin` object and run the code in the `__init__()` method for them. We pass in three integers as arguments to `WizCoin()`, which are forwarded to the parameters of `__init__()`. These arguments are assigned to the object's `self.galleons`, `self.sickles`, and `self.knuts` attributes. Note that, just as the `time.sleep()` function requires you to first import the `time` module and put `time.` before the function name, we must also import `wizcoin` and put `wizcoin.` before the `WizCoin()` function name.

When you run this program, the output will look something like this:

---

```
<wizcoin.WizCoin object at 0x000002136F138080>
G: 2 S: 5 K: 99
Total value: 1230
Weight: 613.906 grams

<wizcoin.WizCoin object at 0x000002136F138128>
G: 13 S: 0 K: 0
Total value: 6409
Weight: 404.339 grams
```

---

If you get an error message, such as `ModuleNotFoundError: No module named 'wizcoin'`, check to make sure that your file is named *wizcoin.py* and that it's in the same folder as *wcexample1.py*.

The `WizCoin` objects don't have useful string representations, so printing `purse` and `coinJar` displays a memory address in between angle brackets. (You'll learn how to change this in Chapter 17.)

Just as we can call the `lower()` string method on a string object, we can call the `value()` and `weightInGrams()` methods on the `WizCoin` objects we've