

```

    @property
    ④ def galleons(self):
        """Returns the number of galleon coins in this object."""
        return self._galleons

    @galleons.setter
    ⑤ def galleons(self, value):
    ⑥         if not isinstance(value, int):
    ⑦             raise WizCoinException('galleons attr must be set to an int, not a '
+ value.__class__.__qualname__)
    ⑧         if value < 0:
            raise WizCoinException('galleons attr must be a positive int, not ' +
value.__class__.__qualname__)
            self._galleons = value

--snip--

```

The new changes add a `WizCoinException` class ❶ that inherits from Python's built-in `Exception` class. The class's docstring describes how the `wizcoin` module ❷ uses it. This is a best practice for Python modules: the `WizCoin` class's objects can raise this when they're misused. That way, if a `WizCoin` object raises other exception classes, like `ValueError` or `TypeError`, this will mostly likely signify that it's a bug in the `WizCoin` class.

In the `__init__()` method, we set the `self.galleons`, `self.sickles`, and `self.knuts` properties ❸ to the corresponding parameters.

At the bottom of the file, after the `total()` and `weight()` methods, we add a getter ❹ and setter method ❺ for the `self._galleons` attribute. The getter simply returns the value in `self._galleons`. The setter checks whether the value being assigned to the `galleons` property is an integer ❻ and positive ❼. If either check fails, `WizCoinException` is raised with an error message. This check prevents `_galleons` from ever being set with an invalid value as long as code always uses the `galleons` property.

All Python objects automatically have a `__class__` attribute, which refers to the object's class object. In other words, `value.__class__` is the same class object that `type(value)` returns. This class object has an attribute named `__qualname__` that is a string of the class's name. (Specifically, it's the *qualified* name of the class, which includes the names of any classes the class object is nested in. Nested classes are of limited use and beyond the