

- `purse == [2, 5, 10]` is the same as `[2, 5, 10] == purse`
- `purse != [2, 5, 10]` is the same as `[2, 5, 10] != purse`

Once you've implemented the comparison dunder methods, Python's `sort()` function will automatically use them to sort your objects. Enter the following into the interactive shell:

```
>>> import wizcoin
>>> oneGalleon = wizcoin.WizCoin(1, 0, 0) # Worth 493 knuts.
>>> oneSickle = wizcoin.WizCoin(0, 1, 0) # Worth 29 knuts.
>>> oneKnut = wizcoin.WizCoin(0, 0, 1) # Worth 1 knut.
>>> coins = [oneSickle, oneKnut, oneGalleon, 100]
>>> coins.sort() # Sort them from lowest value to highest.
>>> coins
[WizCoin(0, 0, 1), WizCoin(0, 1, 0), 100, WizCoin(1, 0, 0)]
```

[Table 17-3](#) contains a full listing of the available comparison dunder methods and operator functions.

[Table 17-3:](#) Comparison Dunder Methods and operator Module Functions

Dunder method	Operation	Comparison operator	Function in operator module
<code>__eq__()</code>	E qual	<code>==</code>	<code>operator.eq()</code>
<code>__ne__()</code>	N ot Equal	<code>!=</code>	<code>operator.ne()</code>
<code>__lt__()</code>	L ess Than	<code><</code>	<code>operator.lt()</code>
<code>__le__()</code>	L ess than or E qual	<code><=</code>	<code>operator.le()</code>
<code>__gt__()</code>	G reater Than	<code>></code>	<code>operator.gt()</code>
<code>__ge__()</code>	G reater than or E qual	<code>>=</code>	<code>operator.ge()</code>

You can see the implementation for these methods at <https://autbor.com/wizcoinfull>. The full documentation for the comparison dunder methods is in the Python documentation at https://docs.python.org/3/reference/datamodel.html#object.__lt__.

The comparison dunder methods let objects of your classes use Python's comparison operators rather than forcing you to create your own methods. If you're creating methods named `equals()` or `isGreaterThan()`, they're not