
```
cd C:\Windows\System32
calc.exe
```

- Enter the full file path for the executable program file. For example, instead of entering `calc.exe`, you could enter `C:\Windows\System32\calc.exe`.

On Windows, if a program ends with the file extension `.exe` or `.bat`, including the extension is optional: entering `calc` does the same thing as entering `calc.exe`. Executable programs in macOS and Linux often don't have file extensions marking them as executable; rather, they have the executable permission set. “Running Python Programs Without the Command Line” on page 39 has more information.

Using Command Line Arguments

Command line arguments are bits of text you enter after the command name. Like the arguments passed to a Python function call, they provide the command with specific options or additional directions. For example, when you run the command `cd C:\Users`, the `C:\Users` part is an argument to the `cd` command that tells `cd` to which folder to change the cwd. Or, when you run a Python script from a terminal window with the `python yourScript.py` command, the `yourScript.py` part is an argument telling the `python` program what file to look in for the instructions it should carry out.

Command line options (also called flags, switches, or simply options) are a single-letter or short-word command line arguments. On Windows, command line options often begin with a forward slash (/); on macOS and Linux, they begin with a single dash (-) or double dash (--). You already used the `-a` option when running the macOS command `open -a Calculator`. Command line options are often case sensitive on macOS and Linux but are case insensitive on Windows, and we separate multiple command line options with spaces.

Folders and filenames are common command line arguments. If the folder or filename has a space as part of its name, enclose the name in double quotes to avoid confusing the command line. For example, if you want to change directories to a folder called *Vacation Photos*, entering `cd Vacation Photos` would make the command line think you were passing two arguments, `Vacation` and `Photos`. Instead, you enter `cd "Vacation Photos"`: