

display a small menu under your words as you type them, letting you select one to autocomplete the rest of the command.

Viewing the Command History

In their *command history*, modern shells also remember the commands you've entered. Pressing the up arrow key in the terminal fills the command line with the last command you entered. You can continue to press the up arrow key to find earlier commands, or press the down arrow key to return to more recent commands. If you want to cancel the command currently in the prompt and start from a fresh prompt, press CTRL-C.

On Windows, you can view the command history by running `doskey /history`. (The oddly named *doskey* program goes back to Microsoft's pre-Windows operating system, MS-DOS.) On macOS and Linux, you can view the command history by running the `history` command.

Working with Common Commands

This section contains a short list of the common commands you'll use in the command line. There are far more commands and arguments than listed here, but you can treat these as the bare minimum you'll need to navigate the command line.

Command line arguments for the commands in this section appear between square brackets. For example, `cd [destination folder]` means you should enter `cd`, followed by the name of a new folder.

Match Folder and Filenames with Wildcard Characters

Many commands accept folder and filenames as command line arguments. Often, these commands also accept names with the wildcard characters `*` and `?`, allowing you to specify multiple matching files. The `*` character matches any number of characters, whereas the `?` character matches any single character. We call expressions that use the `*` and `?` wildcard characters *glob patterns* (short for “global patterns”).

Glob patterns let you specify patterns of filenames. For example, you could run the `dir` or `ls` command to display all the files and folders in the `cwd`. But if you wanted to see just the Python files, `dir *.py` or `ls *.py` would