
```
C:\Users\Al>d:
```

```
D:\>cd BackupFiles
```

```
D:\BackupFiles>
```

To change to the parent directory of the cwd, use the `..` folder name:

```
C:\Users\Al>cd ..
```

```
C:\Users>
```

List Folder Contents with `dir` and `ls`

On Windows, the `dir` command displays the folders and files in the cwd. The `ls` command does the same thing on macOS and Linux. You can display the contents of another folder by running `dir [another folder]` or `ls [another folder]`.

The `-l` and `-a` switches are useful arguments for the `ls` command. By default, `ls` displays only the names of files and folders. To display a long listing format that includes file size, permissions, last modification timestamps, and other information, use `-l`. By convention, the macOS and Linux operating systems treat files beginning with a period as configuration files and keep them hidden from normal commands. You can use `-a` to make `ls` display all files, including hidden ones. To display both the long listing format and all files, combine the switches as `ls -al`. Here's an example in a macOS or Linux terminal window:

```
al@ubuntu:~$ ls
Desktop    Downloads      mu_code  Pictures  snap      Videos
Documents  examples.desktop  Music    Public    Templates
al@ubuntu:~$ ls -al
total 112
drwxr-xr-x 18 al   al   4096 Aug  4 18:47 .
drwxr-xr-x  3 root root 4096 Jun 17 18:11 ..
-rw-r--r--  1 al   al   5157 Aug  2 20:43 .bash_history
-rw-r--r--  1 al   al    220 Jun 17 18:11 .bash_logout
-rw-r--r--  1 al   al   3771 Jun 17 18:11 .bashrc
drwxr-xr-x 17 al   al   4096 Jul 30 10:16 .cache
drwxr-xr-x 14 al   al   4096 Jun 19 15:04 .config
```