

Delete Folders with `rd` and `rmdir`

Running `rd [source folder]` deletes the source folder on Windows, and `rmdir [source folder]` deletes the source folder on macOS and Linux. Like `mkdir`, the `rmdir` command also works on Windows, but `rd` is easier to type. The folder must be empty before you can remove it.

Here's an example in a Linux terminal window:

```
al@ubuntu:~/Desktop$ mkdir yourScripts
al@ubuntu:~/Desktop$ ls
yourScripts
al@ubuntu:~/Desktop$ rmdir yourScripts
al@ubuntu:~/Desktop$ ls
al@ubuntu:~/Desktop$
```

In this example, we created an empty folder named *yourScripts* and then removed it.

To delete nonempty folders (along with all the folders and files it contains), run `rd /s/q [source folder]` on Windows or `rm -rf [source folder]` on macOS and Linux.

Find Programs with `where` and `which`

Running `where [program]` on Windows or `which [program]` on macOS and Linux tells you the exact location of the program. When you enter a command on the command line, your computer checks for the program in the folders listed in the `PATH` environment variable (although Windows checks the `cwd` first).

These commands can tell you which executable Python program is run when you enter `python` in the shell. If you have multiple Python versions installed, your computer might have several executable programs of the same name. The one that is run depends on the order of folders in your `PATH` environment variable, and the `where` and `which` commands will output it:

```
C:\Users\Al>where python
C:\Users\Al\AppData\Local\Programs\Python\Python38\python.exe
```
