

```
-weights=[42.0,3.1415,2.718]
+weights = [42.0, 3.1415, 2.718]
```

The minus sign indicates that Black would remove the line `weights=[42.0,3.1415,2.718]` and replace it with the line prefixed with a plus sign: `weights = [42.0, 3.1415, 2.718]`. Keep in mind that once you've run Black to change your source code files, there's no way to undo this change. You need to either make backup copies of your source code or use version control software, such as Git, before running Black.

Disabling Black for Parts of Your Code

As great as Black is, you might not want it to format some sections of your code. For example, I like to do my own special spacing whenever I'm lining up multiple related assignment statements, as in the following example:

```
# Set up constants for different time amounts:
SECONDS_PER_MINUTE = 60
SECONDS_PER_HOUR   = 60 * SECONDS_PER_MINUTE
SECONDS_PER_DAY     = 24 * SECONDS_PER_HOUR
SECONDS_PER_WEEK    = 7  * SECONDS_PER_DAY
```

Black would remove the additional spaces before the `=` assignment operator, making them, in my opinion, less readable:

```
# Set up constants for different time amounts:
SECONDS_PER_MINUTE = 60
SECONDS_PER_HOUR = 60 * SECONDS_PER_MINUTE
SECONDS_PER_DAY = 24 * SECONDS_PER_HOUR
SECONDS_PER_WEEK = 7 * SECONDS_PER_DAY
```

By adding `# fmt: off` and `# fmt: on` comments, we can tell Black to turn off its code formatting for these lines and then resume code formatting afterward:

```
# Set up constants for different time amounts:
# fmt: off
SECONDS_PER_MINUTE = 60
SECONDS_PER_HOUR   = 60 * SECONDS_PER_MINUTE
SECONDS_PER_DAY     = 24 * SECONDS_PER_HOUR
```