

and then have a single `print()` call that runs after the chain has been evaluated:

```
age = 12

if age < 4:
    price = 0
elif age < 18:
    price = 25
else:
    price = 40

print(f"Your admission cost is ${price}.")
```

The indented lines set the value of `price` according to the person's age, as in the previous example. After the price is set by the `if-elif-else` chain, a separate unindented `print()` call uses this value to display a message reporting the person's admission price.

This code produces the same output as the previous example, but the purpose of the `if-elif-else` chain is narrower. Instead of determining a price and displaying a message, it simply determines the admission price. In addition to being more efficient, this revised code is easier to modify than the original approach. To change the text of the output message, you would need to change only one `print()` call rather than three separate `print()` calls.

Using Multiple `elif` Blocks

You can use as many `elif` blocks in your code as you like. For example, if the amusement park were to implement a discount for seniors, you could add one more conditional test to the code to determine whether someone qualifies for the senior discount. Let's say that anyone 65 or older pays half the regular admission, or \$20:

```
age = 12

if age < 4:
    price = 0
elif age < 18:
    price = 25
elif age < 65:
    price = 40
else:
    price = 20

print(f"Your admission cost is ${price}.")
```

Most of this code is unchanged. The second `elif` block now checks to make sure a person is less than age 65 before assigning them the full admission rate of \$40. Notice that the value assigned in the `else` block needs to be changed to \$20, because the only ages that make it to this block are for people 65 or older.