

This returns the value associated with the key 'color' from the dictionary `alien_0`:

```
green
```

You can have an unlimited number of key-value pairs in a dictionary. For example, here's the original `alien_0` dictionary with two key-value pairs:

```
alien_0 = {'color': 'green', 'points': 5}
```

Now you can access either the color or the point value of `alien_0`. If a player shoots down this alien, you can look up how many points they should earn using code like this:

```
alien_0 = {'color': 'green', 'points': 5}

new_points = alien_0['points']
print(f"You just earned {new_points} points!")
```

Once the dictionary has been defined, we pull the value associated with the key 'points' from the dictionary. This value is then assigned to the variable `new_points`. The last line prints a statement about how many points the player just earned:

```
You just earned 5 points!
```

If you run this code every time an alien is shot down, the alien's point value will be retrieved.

Adding New Key-Value Pairs

Dictionaries are dynamic structures, and you can add new key-value pairs to a dictionary at any time. To add a new key-value pair, you would give the name of the dictionary followed by the new key in square brackets, along with the new value.

Let's add two new pieces of information to the `alien_0` dictionary: the alien's *x*- and *y*-coordinates, which will help us display the alien at a particular position on the screen. Let's place the alien on the left edge of the screen, 25 pixels down from the top. Because screen coordinates usually start at the upper-left corner of the screen, we'll place the alien on the left edge of the screen by setting the *x*-coordinate to 0 and 25 pixels from the top by setting its *y*-coordinate to positive 25, as shown here:

```
alien.py alien_0 = {'color': 'green', 'points': 5}
print(alien_0)

alien_0['x_position'] = 0
alien_0['y_position'] = 25
print(alien_0)
```
