

```

while polling_active:
    # Prompt for the person's name and response.
    ❶ name = input("\nWhat is your name? ")
    response = input("Which mountain would you like to climb someday? ")

    # Store the response in the dictionary.
    ❷ responses[name] = response

    # Find out if anyone else is going to take the poll.
    ❸ repeat = input("Would you like to let another person respond? (yes/ no) ")
    if repeat == 'no':
        polling_active = False

# Polling is complete. Show the results.
print("\n--- Poll Results ---")
    ❹ for name, response in responses.items():
        print(f"{name} would like to climb {response}.").

```

The program first defines an empty dictionary (`responses`) and sets a flag (`polling_active`) to indicate that polling is active. As long as `polling_active` is `True`, Python will run the code in the `while` loop.

Within the loop, the user is prompted to enter their name and a mountain they'd like to climb ❶. That information is stored in the `responses` dictionary ❷, and the user is asked whether or not to keep the poll running ❸. If they enter `yes`, the program enters the `while` loop again. If they enter `no`, the `polling_active` flag is set to `False`, the `while` loop stops running, and the final code block ❹ displays the results of the poll.

If you run this program and enter sample responses, you should see output like this:

```

What is your name? Eric
Which mountain would you like to climb someday? Denali
Would you like to let another person respond? (yes/ no) yes

What is your name? Lynn
Which mountain would you like to climb someday? Devil's Thumb
Would you like to let another person respond? (yes/ no) no

--- Poll Results ---
Eric would like to climb Denali.
Lynn would like to climb Devil's Thumb.

```
