

assume is True is actually False, the test will fail and you'll know there's an issue to resolve. Table 11-1 shows some of the most useful kinds of assertions you can include in your initial tests.

Table 11-1: Commonly Used Assertion Statements in Tests

Assertion	Claim
<code>assert a == b</code>	Assert that two values are equal.
<code>assert a != b</code>	Assert that two values are not equal.
<code>assert a</code>	Assert that <code>a</code> evaluates to True.
<code>assert not a</code>	Assert that <code>a</code> evaluates to False.
<code>assert element in list</code>	Assert that an element is in a list.
<code>assert element not in list</code>	Assert that an element is not in a list.

These are just a few examples; anything that can be expressed as a conditional statement can be included in a test.

A Class to Test

Testing a class is similar to testing a function, because much of the work involves testing the behavior of the methods in the class. However, there are a few differences, so let's write a class to test. Consider a class that helps administer anonymous surveys:

```
survey.py class AnonymousSurvey:
    """Collect anonymous answers to a survey question."""

    ❶ def __init__(self, question):
        """Store a question, and prepare to store responses."""
        self.question = question
        self.responses = []

    ❷ def show_question(self):
        """Show the survey question."""
        print(self.question)

    ❸ def store_response(self, new_response):
        """Store a single response to the survey."""
        self.responses.append(new_response)

    ❹ def show_results(self):
        """Show all the responses that have been given."""
        print("Survey results:")
        for response in self.responses:
            print(f"- {response}")
```

This class starts with a survey question that you provide ❶ and includes an empty list to store responses. The class has methods to print the survey question ❷, add a new response to the response list ❸, and print all the responses stored in the list ❹. To create an instance from this class, all you