

have to provide is a question. Once you have an instance representing a particular survey, you display the survey question with `show_question()`, store a response using `store_response()`, and show results with `show_results()`.

To show that the `AnonymousSurvey` class works, let's write a program that uses the class:

```
language _survey.py from survey import AnonymousSurvey

# Define a question, and make a survey.
question = "What language did you first learn to speak?"
language_survey = AnonymousSurvey(question)

# Show the question, and store responses to the question.
language_survey.show_question()
print("Enter 'q' at any time to quit.\n")
while True:
    response = input("Language: ")
    if response == 'q':
        break
    language_survey.store_response(response)

# Show the survey results.
print("\nThank you to everyone who participated in the survey!")
language_survey.show_results()
```

This program defines a question ("What language did you first learn to speak?") and creates an `AnonymousSurvey` object with that question. The program calls `show_question()` to display the question and then prompts for responses. Each response is stored as it is received. When all responses have been entered (the user inputs `q` to quit), `show_results()` prints the survey results:

```
What language did you first learn to speak?
Enter 'q' at any time to quit.
```

```
Language: English
Language: Spanish
Language: English
Language: Mandarin
Language: q
```

```
Thank you to everyone who participated in the survey!
Survey results:
- English
- Spanish
- English
- Mandarin
```

This class works for a simple anonymous survey, but say we want to improve `AnonymousSurvey` and the module it's in, `survey`. We could allow each user to enter more than one response, we could write a method to list only unique responses and to report how many times each response was given, or we could even write another class to manage non-anonymous surveys.