

--snip--

```
def test_store_three_responses():
    """Test that three individual responses are stored properly."""
    question = "What language did you first learn to speak?"
    language_survey = AnonymousSurvey(question)
    ❶ responses = ['English', 'Spanish', 'Mandarin']
    for response in responses:
        language_survey.store_response(response)
    ❷ for response in responses:
        assert response in language_survey.responses
```

We call the new function `test_store_three_responses()`. We create a survey object just like we did in `test_store_single_response()`. We define a list containing three different responses ❶, and then we call `store_response()` for each of these responses. Once the responses have been stored, we write another loop and assert that each response is now in `language_survey.responses` ❷.

When we run the test file again, both tests (for a single response and for three responses) pass:

```
$ pytest test_survey.py
===== test session starts =====
--snip--
test_survey.py .. [100%]
===== 2 passed in 0.01s =====
```

This works perfectly. However, these tests are a bit repetitive, so we'll use another feature of pytest to make them more efficient.

Using Fixtures

In `test_survey.py`, we created a new instance of `AnonymousSurvey` in each test function. This is fine in the short example we're working with, but in a real-world project with tens or hundreds of tests, this would be problematic.

In testing, a *fixture* helps set up a test environment. Often, this means creating a resource that's used by more than one test. We create a fixture in pytest by writing a function with the decorator `@pytest.fixture`. A *decorator* is a directive placed just before a function definition; Python applies this directive to the function before it runs, to alter how the function code behaves. Don't worry if this sounds complicated; you can start to use decorators from third-party packages before learning to write them yourself.

Let's use a fixture to create a single survey instance that can be used in both test functions in `test_survey.py`:

```
import pytest
from survey import AnonymousSurvey

❶ @pytest.fixture
❷ def language_survey():
    """A survey that will be available to all test functions."""
```