

First, we'll import the new Bullet class:

```
alien_invasion.py --snip--
from ship import Ship
from bullet import Bullet
```

Next we'll create the group that holds the bullets in `__init__()`:

```
alien_invasion.py def __init__(self):
    --snip--
    self.ship = Ship(self)
    self.bullets = pygame.sprite.Group()
```

Then we need to update the position of the bullets on each pass through the while loop:

```
alien_invasion.py def run_game(self):
    """Start the main loop for the game."""
    while True:
        self._check_events()
        self.ship.update()
        self.bullets.update()
        self._update_screen()
        self.clock.tick(60)
```

When you call `update()` on a group, the group automatically calls `update()` for each sprite in the group. The line `self.bullets.update()` calls `bullet.update()` for each bullet we place in the group `bullets`.

Firing Bullets

In `AlienInvasion`, we need to modify `_check_keydown_events()` to fire a bullet when the player presses the spacebar. We don't need to change `_check_keyup_events()` because nothing happens when the spacebar is released. We also need to modify `_update_screen()` to make sure each bullet is drawn to the screen before we call `flip()`.

There will be a bit of work to do when we fire a bullet, so let's write a new method, `_fire_bullet()`, to handle this work:

```
alien
_invasion.py def _check_keydown_events(self, event):
    --snip--
    elif event.key == pygame.K_q:
        sys.exit()
    ❶ elif event.key == pygame.K_SPACE:
        self._fire_bullet()

    def _check_keyup_events(self, event):
        --snip--

    def _fire_bullet(self):
        ❷ """Create a new bullet and add it to the bullets group."""
        new_bullet = Bullet(self)
        ❸ self.bullets.add(new_bullet)
```