

TRY IT YOURSELF

13-1. Stars: Find an image of a star. Make a grid of stars appear on the screen.

13-2. Better Stars: You can make a more realistic star pattern by introducing randomness when you place each star. Recall from Chapter 9 that you can get a random number like this:

```
from random import randint
random_number = randint(-10, 10)
```

This code returns a random integer between -10 and 10. Using your code in Exercise 13-1, adjust each star's position by a random amount.

Making the Fleet Move

Now let's make the fleet of aliens move to the right across the screen until it hits the edge, and then make it drop a set amount and move in the other direction. We'll continue this movement until all aliens have been shot down, one collides with the ship, or one reaches the bottom of the screen. Let's begin by making the fleet move to the right.

Moving the Aliens Right

To move the aliens, we'll use an `update()` method in *alien.py*, which we'll call for each alien in the group of aliens. First, add a setting to control the speed of each alien:

```
settings.py    def __init__(self):
                --snip--
                # Alien settings
                self.alien_speed = 1.0
```

Then use this setting to implement `update()` in *alien.py*:

```
alien.py       def __init__(self, ai_game):
                """Initialize the alien and set its starting position."""
                super().__init__()
                self.screen = ai_game.screen
                self.settings = ai_game.settings
                --snip--

                def update(self):
                    """Move the alien to the right."""
                    ❶ self.x += self.settings.alien_speed
                    ❷ self.rect.x = self.x
```

We create a settings parameter in `__init__()` so we can access the alien's speed in `update()`. Each time we update an alien's position, we move it to the