

Next, we build a reader object ❷. This is an object that can be used to parse each line in the file. To make a reader object, call the function `csv.reader()` and pass it the list of lines from the CSV file.

When given a reader object, the `next()` function returns the next line in the file, starting from the beginning of the file. Here we call `next()` only once, so we get the first line of the file, which contains the file headers ❸. We assign the data that's returned to `header_row`. As you can see, `header_row` contains meaningful, weather-related headers that tell us what information each line of data holds:

```
['STATION', 'NAME', 'DATE', 'TAVG', 'TMAX', 'TMIN']
```

The reader object processes the first line of comma-separated values in the file and stores each value as an item in a list. The header `STATION` represents the code for the weather station that recorded this data. The position of this header tells us that the first value in each line will be the weather station code. The `NAME` header indicates that the second value in each line is the name of the weather station that made the recording. The rest of the headers specify what kinds of information were recorded in each reading. The data we're most interested in for now are the date (`DATE`), the high temperature (`TMAX`), and the low temperature (`TMIN`). This is a simple dataset that contains only temperature-related data. When you download your own weather data, you can choose to include a number of other measurements relating to wind speed, wind direction, and precipitation data.

Printing the Headers and Their Positions

To make it easier to understand the file header data, let's print each header and its position in the list:

```
sitka_highs.py  --snip--
reader = csv.reader(lines)
header_row = next(reader)

for index, column_header in enumerate(header_row):
    print(index, column_header)
```

The `enumerate()` function returns both the index of each item and the value of each item as you loop through a list. (Note that we've removed the line `print(header_row)` in favor of this more detailed version.)

Here's the output showing the index of each header:

```
0 STATION
1 NAME
2 DATE
3 TAVG
4 TMAX
5 TMIN
```
