

First, let's run the code to see the headers that are included in this data file:

```
death_valley
_highs_lows.py from pathlib import Path
import csv

path = Path('weather_data/death_valley_2021_simple.csv')
lines = path.read_text().splitlines()

reader = csv.reader(lines)
header_row = next(reader)

for index, column_header in enumerate(header_row):
    print(index, column_header)
```

Here's the output:

```
0 STATION
1 NAME
2 DATE
3 TMAX
4 TMIN
5 TOBS
```

The date is in the same position, at index 2. But the high and low temperatures are at indexes 3 and 4, so we'll need to change the indexes in our code to reflect these new positions. Instead of including an average temperature reading for the day, this station includes `TOBS`, a reading for a specific observation time.

Change *sitka_highs_lows.py* to generate a graph for Death Valley using the indexes we just noted, and see what happens:

```
death_valley
_highs_lows.py --snip--
path = Path('weather_data/death_valley_2021_simple.csv')
lines = path.read_text().splitlines()
--snip--
# Extract dates, and high and low temperatures.
dates, highs, lows = [], [], []
for row in reader:
    current_date = datetime.strptime(row[2], '%Y-%m-%d')
    high = int(row[3])
    low = int(row[4])
    dates.append(current_date)
--snip--
```

We update the program to read from the Death Valley data file, and we change the indexes to correspond to this file's `TMAX` and `TMIN` positions.

When we run the program, we get an error:

```
Traceback (most recent call last):
  File "death_valley_highs_lows.py", line 17, in <module>
    high = int(row[3])
❶ ValueError: invalid literal for int() with base 10: ''
```
