

```

❶ print(f"Total repositories: {response_dict['total_count']}")
   print(f"Complete results: {not response_dict['incomplete_results']}")

   # Explore information about the repositories.
❷ repo_dicts = response_dict['items']
   print(f"Repositories returned: {len(repo_dicts)}")

   # Examine the first repository.
❸ repo_dict = repo_dicts[0]
❹ print(f"\nKeys: {len(repo_dict)}")
❺ for key in sorted(repo_dict.keys()):
    print(key)

```

We start exploring the response dictionary by printing the value associated with 'total_count', which represents the total number of Python repositories returned by this API call ❶. We also use the value associated with 'incomplete_results', so we'll know if GitHub was able to fully process the query. Rather than printing this value directly, we print its opposite: a value of True will indicate that we received a complete set of results.

The value associated with 'items' is a list containing a number of dictionaries, each of which contains data about an individual Python repository. We assign this list of dictionaries to `repo_dicts` ❷. We then print the length of `repo_dicts` to see how many repositories we have information for.

To look closer at the information returned about each repository, we pull out the first item from `repo_dicts` and assign it to `repo_dict` ❸. We then print the number of keys in the dictionary to see how much information we have ❹. Finally, we print all the dictionary's keys to see what kind of information is included ❺.

The results give us a clearer picture of the actual data:

```

Status code: 200
❶ Total repositories: 248
❷ Complete results: True
   Repositories returned: 30

❸ Keys: 78
   allow_forking
   archive_url
   archived
   --snip--
   url
   visibility
   watchers
   watchers_count

```

At the time of this writing, there are only 248 Python repositories with over 10,000 stars ❶. We can see that GitHub was able to fully process the API call ❷. In this response, GitHub returned information about the first 30 repositories that match the conditions of our query. If we want more repositories, we can request additional pages of data.