

```
Apply all migrations: admin, auth, contenttypes, sessions
Running migrations:
  Applying contenttypes.0001_initial... OK
  Applying auth.0001_initial... OK
  --snip--
  Applying sessions.0001_initial... OK
❷ (ll_env)learning_log$ ls
db.sqlite3 ll_env ll_project manage.py
```

Anytime we modify a database, we say we're *migrating* the database. Issuing the migrate command for the first time tells Django to make sure the database matches the current state of the project. The first time we run this command in a new project using SQLite (more about SQLite in a moment), Django will create a new database for us. Here, Django reports that it will prepare the database to store information it needs to handle administrative and authentication tasks ❶.

Running the ls command shows that Django created another file called *db.sqlite3* ❷. *SQLite* is a database that runs off a single file; it's ideal for writing simple apps because you won't have to pay much attention to managing the database.

NOTE

In an active virtual environment, use the command `python` to run `manage.py` commands, even if you use something different, like `python3`, to run other programs. In a virtual environment, the command `python` refers to the version of Python that was used to create the virtual environment.

Viewing the Project

Let's make sure that Django has set up the project properly. Enter the **runserver** command to view the project in its current state:

```
(ll_env)learning_log$ python manage.py runserver
Watching for file changes with StatReloader
Performing system checks...
```

- ❶ System check identified no issues (0 silenced).
 - May 19, 2022 - 21:52:35
 - ❷ Django version 4.1, using settings 'll_project.settings'
 - ❸ Starting development server at http://127.0.0.1:8000/
Quit the server with CONTROL-C.
-

Django should start a server called the *development server*, so you can view the project on your system to see how well it works. When you request a page by entering a URL in a browser, the Django server responds to that request by building the appropriate page and sending it to the browser.

Django first checks to make sure the project is set up properly ❶; it then reports the version of Django in use and the name of the settings file in use ❷. Finally, it reports the URL where the project is being served ❸. The URL *http://127.0.0.1:8000/* indicates that the project is listening for requests on port 8000 on your computer, which is called a localhost. The