

The new URL pattern is the word *topics*, followed by a forward slash. When Django examines a requested URL, this pattern will match any URL that has the base URL followed by *topics*. You can include or omit a forward slash at the end, but there can't be anything else after the word *topics*, or the pattern won't match. Any request with a URL that matches this pattern will then be passed to the function `topics()` in *views.py*.

The Topics View

The `topics()` function needs to retrieve some data from the database and send it to the template. Add the following to *views.py*:

```
views.py  from django.shortcuts import render

❶ from .models import Topic

    def index(request):
        --snip--

❷ def topics(request):
    """Show all topics."""
❸     topics = Topic.objects.order_by('date_added')
❹     context = {'topics': topics}
❺     return render(request, 'learning_logs/topics.html', context)
```

We first import the model associated with the data we need ❶. The `topics()` function needs one parameter: the request object Django received from the server ❷. We query the database by asking for the `Topic` objects, sorted by the `date_added` attribute ❸. We assign the resulting queryset to `topics`.

We then define a context that we'll send to the template ❹. A *context* is a dictionary in which the keys are names we'll use in the template to access the data we want, and the values are the data we need to send to the template. In this case, there's one key-value pair, which contains the set of topics we'll display on the page. When building a page that uses data, we call `render()` with the request object, the template we want to use, and the context dictionary ❺.

The Topics Template

The template for the topics page receives the context dictionary, so the template can use the data that `topics()` provides. Make a file called *topics.html* in the same directory as *index.html*. Here's how we can display the topics in the template:

```
topics.html  {% extends 'learning_logs/base.html' %}

    {% block content %}

        <p>Topics</p>
```