

```

❶ <ul>
❷     {% for topic in topics %}
❸     <li>{{ topic.text }}</li>
❹     {% empty %}
        <li>No topics have been added yet.</li>
❺     {% endfor %}
❻ </ul>

{% endblock content %}

```

---

We use the `{% extends %}` tag to inherit from *base.html*, just as we did on the home page, and then we open a content block. The body of this page contains a bulleted list of the topics that have been entered. In standard HTML, a bulleted list is called an *unordered list* and is indicated by the tags `<ul></ul>`. The opening tag `<ul>` begins the bulleted list of topics ❶.

Next we use a template tag that's equivalent to a `for` loop, which loops through the list topics from the context dictionary ❷. The code used in templates differs from Python in some important ways. Python uses indentation to indicate which lines of a `for` statement are part of a loop. In a template, every `for` loop needs an explicit `{% endfor %}` tag indicating where the end of the loop occurs. So in a template, you'll see loops written like this:

```

{% for item in list %}
    do something with each item
{% endfor %}

```

---

Inside the loop, we want to turn each topic into an item in the bulleted list. To print a variable in a template, wrap the variable name in double braces. The braces won't appear on the page; they just indicate to Django that we're using a template variable. So the code `{{ topic.text }}` ❸ will be replaced by the value of the current topic's text attribute on each pass through the loop. The HTML tag `<li></li>` indicates a *list item*. Anything between these tags, inside a pair of `<ul></ul>` tags, will appear as a bulleted item in the list.

We also use the `{% empty %}` template tag ❹, which tells Django what to do if there are no items in the list. In this case, we print a message informing the user that no topics have been added yet. The last two lines close out the `for` loop ❺ and then close out the bulleted list ❻.

Now we need to modify the base template to include a link to the topics page. Add the following code to *base.html*:

```

base.html <p>
❶ <a href="{% url 'learning_logs:index' %}">Learning Log</a> -
❷ <a href="{% url 'learning_logs:topics' %}">Topics</a>
</p>

{% block content %}{% endblock content %}

```

---

We add a dash after the link to the home page ❶, and then add a link to the topics page using the `{% url %}` template tag again ❷. This line tells