

③ {% block content %}{% endblock content %}

```
</body>
</html>
```

---

The first new element is the opening `<body>` tag. The *body* of an HTML file contains the content users will see on a page. Next we have a `<nav>` element, which opens the code for the navigation bar at the top of the page ❶. Everything contained in this element is styled according to the Bootstrap style rules defined by the selectors `navbar`, `navbar-expand-md`, and the rest that you see here. A *selector* determines which elements on a page a certain style rule applies to. The `navbar-light` and `bg-light` selectors style the navigation bar with a light-themed background. The `mb` in `mb-4` is short for *margin-bottom*; this selector ensures that a little space appears between the navigation bar and the rest of the page. The `border` selector provides a thin border around the light background to set it off a little from the rest of the page.

The `<div>` tag on the next line opens a resizable container that will hold the overall navigation bar. The term *div* is short for *division*; you build a web page by dividing it into sections and defining style and behavior rules that apply to that section. Any styling or behavior rules that are defined in an opening `<div>` tag affect everything you see until its corresponding closing tag, written as `</div>`.

Next we set the project's name, *Learning Log*, to appear as the first element on the navigation bar ❷. This will also serve as a link to the home page, just as it's been doing in the minimally styled version of the project we built in the previous two chapters. The `navbar-brand` selector styles this link so it stands out from the rest of the links and helps add some branding to the site.

The Bootstrap template then defines a button that appears if the browser window is too narrow to display the whole navigation bar horizontally ❸. When the user clicks the button, the navigation elements appear in a drop-down list. The `collapse` reference causes the navigation bar to collapse when the user shrinks the browser window or when the site is displayed on devices with small screens.

Next, we open a new section (`<div>`) of the navigation bar ❹. This is the part of the navigation bar that can collapse depending on the size of the browser window.

Bootstrap defines navigation elements as items in an unordered list ❺, with style rules that make it look nothing like a list. Every link or element you need on the bar can be included as an item in an unordered list ❻. Here, the only item in the list is our link to the topics page ❼. Notice the closing `</li>` tag at the end of the link; every opening tag needs a corresponding closing tag.

The rest of the lines shown here close out all of the tags that have been opened. In HTML, a comment is written like this:

---

```
<!-- This is an HTML comment. -->
```

---