

Closing tags don't usually have comments, but if you're new to HTML, it can be really helpful to label some of your closing tags. A single missing tag or an extra tag can throw off the layout of an entire page. We include the content block ❸ and the closing `</body>` and `</html>` tags as well.

We're not finished with the navigation bar, but we now have a complete HTML document. If runserver is currently active, stop the current server and restart it. Go to the project's home page, and you should see a navigation bar that has some of the elements shown in Figure 20-1. Now let's add the rest of the elements to the navigation bar.

Adding User Account Links

We still need to add the links associated with user accounts. We'll start by adding all of the account-related links except the logout form.

Make the following changes to *base.html*:

```
base.html      --snip--
               </ul> <!-- End of links on left side of navbar -->

               <!-- Account-related links -->
❶ <ul class="navbar-nav ms-auto mb-2 mb-md-0">

❷     {% if user.is_authenticated %}
       <li class="nav-item">
❸         <span class="navbar-text me-2">Hello, {{ user.username }}.
           </span></li>
❹     {% else %}
       <li class="nav-item">
           <a class="nav-link" href="{% url 'accounts:register' %}">
               Register</a></li>
       <li class="nav-item">
           <a class="nav-link" href="{% url 'accounts:login' %}">
               Log in</a></li>
       {% endif %}

               </ul> <!-- End of account-related links -->

               </div> <!-- Closes collapsible parts of navbar -->
               --snip--
```

We begin a new set of links by using another opening `<ul>` tag ❶. You can have as many groups of links as you need on a page. The selector `ms-auto` is short for *margin-start-automatic*: this selector examines the other elements in the navigation bar and works out a left (start) margin that pushes this group of links to the right side of the browser window.

The `if` block is the same conditional block we used earlier to display appropriate messages to users, depending on whether they're logged in ❷. The block is a little longer now because there are some styling rules inside the conditional tags. The greeting for authenticated users is wrapped in a `<span>` element ❸. A *span element* styles pieces of text or elements of a page that are part of a longer line. While `div` elements create their own divisions in a page, `span` elements are continuous within a larger section. This can