

```

        root: "static"
        expires: 1h
        allow: true

# The size of the persistent disk of the application (in MB).
❹ disk: 512

```

When you save this file, make sure you include the dot at the beginning of the filename. If you omit the dot, Platform.sh won't find the file and your project will not be deployed.

You don't need to understand everything in *.platform.app.yaml* at this point; I'll highlight the most important parts of the configuration. The file starts off by specifying the name of the project, which we're calling 'll_project' to be consistent with the name we used when starting the project ❶. We also need to specify the version of Python we're using (3.10 at the time of this writing). You can find a list of supported versions at <https://docs.platform.sh/languages/python.html>.

Next is a section labeled *relationships* that defines other services the project needs ❷. Here the only relationship is to a Postgres database. After that is the *web* section ❸. The *commands:start* section tells Platform.sh what process to use to serve incoming requests. Here we're specifying that gunicorn will handle requests ❹. This command takes the place of the *python manage.py runserver* command we've been using locally.

The *locations* section tells Platform.sh where to send incoming requests ❺. Most requests should be passed through to gunicorn; our *urls.py* files will tell gunicorn exactly how to handle those requests. Requests for static files will be handled separately and will be refreshed once an hour. The last line shows that we're requesting 512MB of disk space on one of Platform.sh's servers ❻.

The rest of *.platform.app.yaml* is as follows:

```

--snip--
disk: 512

# Set a local read/write mount for logs.
❶ mounts:
    "logs":
        source: local
        source_path: logs

# The hooks executed at various points in the lifecycle of the application.
❷ hooks:
    build: |
❸      pip install --upgrade pip
        pip install -r requirements.txt
        pip install -r requirements_remote.txt

        mkdir logs
❹      python manage.py collectstatic
        rm -rf logs
❺      deploy: |
        python manage.py migrate

```
