

NOTE

If you're using macOS, add `.DS_Store` to your `.gitignore` file. This is a file that stores information about folder settings on macOS, and it has nothing to do with this project.

Committing the Project

We need to initialize a Git repository for Learning Log, add all the necessary files to the repository, and commit the initial state of the project. Here's how to do that:

```
❶ (ll_env)learning_log$ git init
Initialized empty Git repository in /Users/eric/.../learning_log/.git/
❷ (ll_env)learning_log$ git add .
❸ (ll_env)learning_log$ git commit -am "Ready for deployment to Platform.sh."
[main (root-commit) c7ffaad] Ready for deployment to Platform.sh.
 42 files changed, 879 insertions(+)
   create mode 100644 .gitignore
   create mode 100644 .platform.app.yaml
   --snip--
   create mode 100644 requirements_remote.txt
❹ (ll_env)learning_log$ git status
On branch main
nothing to commit, working tree clean
(ll_env)learning_log$
```

We issue the `git init` command to initialize an empty repository in the directory containing Learning Log ❶. We then use the `git add .` command, which adds all the files that aren't being ignored to the repository ❷. (Don't forget the dot.) Next, we issue the command `git commit -am "commit message"`: the `-a` flag tells Git to include all changed files in this commit, and the `-m` flag tells Git to record a log message ❸.

Issuing the `git status` command ❹ indicates that we're on the *main* branch and that our working tree is *clean*. This is the status you'll want to see anytime you push your project to a remote server.

Creating a Project on Platform.sh

At this point, the Learning Log project still runs on our local system and is also configured to run correctly on a remote server. We'll use the Platform.sh CLI to create a new project on the server and then push our project to the remote server.

Make sure you're in a terminal, at the *learning_log/* directory, and issue the following command:

```
(ll_env)learning_log$ platform login
Opened URL: http://127.0.0.1:5000
Please use the browser to log in.
--snip--
❶ Do you want to create an SSH configuration file automatically? [Y/n] Y
```
