

This command will open a browser tab where you can log in. Once you're logged in, you can close the browser tab and return to the terminal. If you're prompted about creating an SSH configuration file ❶, enter **Y** so you can connect to the remote server later.

Now we'll create a project. There's a lot of output, so we'll look at the creation process in sections. Start by issuing the **create** command:

```
(ll_env)learning_log$ platform create
* Project title (--title)
Default: Untitled Project
❶ > ll_project

* Region (--region)
The region where the project will be hosted
--snip--
[us-3.platform.sh] Moses Lake, United States (AZURE) [514 gCO2eq/kWh]
❷ > us-3.platform.sh

* Plan (--plan)
Default: development
Enter a number to choose:
[0] development
--snip--
❸ > 0

* Environments (--environments)
The number of environments
Default: 3
❹ > 3

* Storage (--storage)
The amount of storage per environment, in GiB
Default: 5
❺ > 5
```

The first prompt asks for a name for the project ❶, so we use the name **ll_project**. The next prompt asks which region we'd like the server to be in ❷. Choose the server closest to you; for me, that's **us-3.platform.sh**. For the rest of the prompts, you can accept the defaults: a server on the lowest development plan ❸, three environments for the project ❹, and 5GB of storage for the overall project ❺.

There are three more prompts to respond to:

```
Default branch (--default-branch)
The default Git branch name for the project (the production environment)
Default: main
❶ > main

Git repository detected: /Users/eric/.../learning_log
❷ Set the new project ll_project as the remote for this repository? [Y/n] Y

The estimated monthly cost of this project is: $10 USD
❸ Are you sure you want to continue? [Y/n] Y
```