

The Platform.sh Bot is activating your project



The project is now ready!

A Git repository can have multiple branches; Platform.sh is asking us if the default branch for the project should be main ❶. It then asks if we want to connect the local project's repository to the remote repository ❷. Finally, we're informed that this project will cost about \$10 per month if we keep it running beyond the free trial period ❸. If you haven't entered a credit card yet, you shouldn't have to worry about this cost. Platform.sh will simply suspend your project if you exceed the free trial's limits without adding a credit card.

Pushing to Platform.sh

The last step before seeing the live version of the project is to push our code to the remote server. To do that, issue the following command:

```
(ll_env)learning_log$ platform push
❶ Are you sure you want to push to the main (production) branch? [Y/n] Y
--snip--
The authenticity of host 'git.us-3.platform.sh (...)' can't be established.
RSA key fingerprint is SHA256:Tvn...7PM
❷ Are you sure you want to continue connecting (yes/no/[fingerprint])? Y
Pushing HEAD to the existing environment main
--snip--
To git.us-3.platform.sh:3pp3mqcexhlvy.git
* [new branch]      HEAD -> main
```

When you issue the command **platform push**, you'll be asked for one more confirmation that you want to push the project ❶. You may also see a message about the authenticity of Platform.sh, if this is your first time connecting to the site ❷. Enter **Y** for each of these prompts, and you'll see a bunch of output scroll by. This output will probably look confusing at first, but if anything goes wrong, it's really useful to have during troubleshooting. If you skim through the output, you can see where Platform.sh installs necessary packages, collects static files, applies migrations, and sets up URLs for the project.

NOTE

*You may see an error from something that you can easily diagnose, such as a typo in one of the configuration files. If this happens, fix the error in your text editor, save the file, and reissue the **git commit** command. Then you can run **platform push** again.*