

Deleting a Project on Platform.sh

It's great practice to run through the deployment process a number of times with the same project or with a series of small projects, to get the hang of deployment. But you'll need to know how to delete a project that's been deployed. Platform.sh also limits the number of projects you can host for free, and you don't want to clutter your account with practice projects.

You can delete a project using the CLI:

```
(ll_env)learning_log$ platform project:delete
```

You'll be asked to confirm that you want to take this destructive action. Respond to the prompts, and your project will be deleted.

The command `platform create` also gave the local Git repository a reference to the remote repository on Platform.sh's servers. You can remove this remote from the command line as well:

```
(ll_env)learning_log$ git remote  
platform  
(ll_env)learning_log$ git remote remove platform
```

The command `git remote` lists the names of all remote URLs associated with the current repository. The command `git remote remove remote_name` deletes these remote URLs from the local repository.

You can also delete a project's resources by logging in to the Platform.sh website and visiting your dashboard at <https://console.platform.sh>. This page lists all your active projects. Click the three dots in a project's box, and click **Edit Plan**. This is a pricing page for the project; click the **Delete Project** button at the bottom of the page, and you'll be shown a confirmation page where you can follow through with the deletion. Even if you deleted your project using the CLI, it's a good idea to familiarize yourself with the dashboard of any hosting provider you deploy to.

NOTE

Deleting a project on Platform.sh does nothing to your local version of the project. If no one has used your deployed project and you're just practicing the deployment process, it's perfectly reasonable to delete your project on Platform.sh and redeploy it. Just be aware that if things stop working, you may have run into the host's free-tier limitations.

TRY IT YOURSELF

20-3. Live Blog: Deploy the Blog project you've been working on to Platform.sh. Make sure you set `DEBUG` to `False`, so users don't see the full Django error pages when something goes wrong.

(continued)