

Editor: Rulers; click the link labeled *Edit in settings.json*. In the file that appears, add the following to the `editor.rulers` setting:

settings.json

```
"editor.rulers": [  
    80,  
]
```

This will add a vertical line in the editing window at the 80-character position. You can have more than one vertical line; for example, if you want an additional line at 120 characters, the value for your setting would be `[80, 120]`. If you don't see the vertical lines, make sure you saved the settings file; you may also need to quit and reopen VS Code for the changes to take effect on some systems.

Simplifying the Output

By default, VS Code shows the output of your programs in an embedded terminal window. This output includes the commands that are being used to run the file. For many situations, this is ideal, but it might be more distracting than you want when you're first learning Python.

To simplify the output, close all the tabs that are open in VS Code and then quit VS Code. Launch VS Code again and open the folder that contains the Python files you're working on; this could just be the *python_work* folder where *hello_world.py* is saved.

Click the Run/Debug icon (which looks like a triangle with a small bug), and then click **Create a launch.json File**. Select the Python options in the prompts that appear. In the *launch.json* file that opens, make the following change:

launch.json

```
{  
    --snip--  
    "configurations": [  
        {  
            --snip--  
            "console": "internalConsole",  
            "justMyCode": true  
        }  
    ]  
}
```

Here, we're changing the console setting from `integratedTerminal` to `internalConsole`. After saving the settings file, open a *.py* file such as *hello_world.py*, and run it by pressing CTRL-F5. In the output pane of VS Code, click **Debug Console** if it's not already selected. You should see only your program's output, and the output should be refreshed every time you run a program.

NOTE

The Debug Console is read-only. It won't work for files that use the `input()` function, which you'll start using in Chapter 7. When you need to run these programs, you can either change the console setting back to the default `integratedTerminal`, or you can run these programs in a separate terminal window as described in "Running Python Programs from a Terminal" on page 11.