

- ③ last = theString[-1]
- ④ return head == last and isPalindrome(middle)

```
text = 'racecar'
print(text + ' is a palindrome: ' + str(isPalindrome(text)))
text = 'amanaplanacanalpanama'
print(text + ' is a palindrome: ' + str(isPalindrome(text)))
text = 'tacocat'
print(text + ' is a palindrome: ' + str(isPalindrome(text)))
text = 'zophie'
print(text + ' is a palindrome: ' + str(isPalindrome(text)))
```

Here is the equivalent JavaScript code in *palindrome.html*:

JavaScript

```
<script type="text/javascript">
function isPalindrome(theString) {
    if (theString.length === 0 || theString.length === 1) {
        // BASE CASE
        return true;
    } else {
        // RECURSIVE CASE
        ① var head = theString[0];
        ② var middle = theString.substring(1, theString.length
-1);
        ③ var last = theString[theString.length - 1];
        ④ return head === last && isPalindrome(middle);
    }
}

text = "racecar";
document.write(text + " is a palindrome: " + isPalindrome(text) + "<br />");
text = "amanaplanacanalpanama";
document.write(text + " is a palindrome: " + isPalindrome(text) + "<br />");
text = "tacocat";
document.write(text + " is a palindrome: " + isPalindrome(text) + "<br />");
text = "zophie";
document.write(text + " is a palindrome: " + isPalindrome(text) + "<br />");
</script>
```
