

```

        solve(numberOfDisks - 1, tempTower, endTower, startTo
wer) ❹
        return

# Solve:
printTowers()
solve(TOTAL_DISKS, 'A', 'B', 'C')

# Uncomment to enable interactive mode:
#while True:
#    printTowers()
#    print('Enter letter of start tower and the end tower.
(A, B, C) Or Q to quit.')
#    move = input().upper()
#    if move == 'Q':
#        sys.exit()
#    elif move[0] in 'ABC' and move[1] in 'ABC' and move[0] !
= move[1]:
#        moveOneDisk(move[0], move[1])

```

This *towerOfHanoiSolver.html* program contains the equivalent JavaScript code:

```

<script type="text/javascript">
// Set up towers A, B, and C. The end of the array is the top
of the tower.
var TOTAL_DISKS = 6; ❶
var TOWERS = {"A": [], ❷
              "B": [],
              "C": []};

// Populate Tower A:
for (var i = TOTAL_DISKS; i > 0; i--) {
    TOWERS["A"].push(i);
}

function printDisk(diskNum) {
    // Print a single disk of width diskNum.
    var emptySpace = " ".repeat(TOTAL_DISKS - diskNum);
    if (diskNum === 0) {
        // Just draw the pole.
        document.write(emptySpace + "||" + emptySpace);
    } else {
        // Draw the disk.
    }
}

```