

```
list('..#.....#...#####...'),
list('..#.....#####...#####...#...'),
list('..#.....#.....#.....#...'),
list('..#.....#####.....#####...'),
list('..#####.....#.....'),
list('.....#...#####.....#####.....'),
list('.....#####.....#####.....')]
```

```
HEIGHT = len(im)
WIDTH = len(im[0])
```

```
def floodFill(image, x, y, newChar, oldChar=None):
    if oldChar == None:
        # oldChar defaults to the character at x, y.
        ❷ oldChar = image[y][x]
    if oldChar == newChar or image[y][x] != oldChar:
        # BASE CASE
        return

    image[y][x] = newChar # Change the character.

    # Uncomment to view each step:
    #printImage(image)

    # Change the neighboring characters.
    if y + 1 < HEIGHT and image[y + 1][x] == oldChar:
        # RECURSIVE CASE
        ❸ floodFill(image, x, y + 1, newChar, oldChar)
    if y - 1 >= 0 and image[y - 1][x] == oldChar:
        # RECURSIVE CASE
        ❹ floodFill(image, x, y - 1, newChar, oldChar)
    if x + 1 < WIDTH and image[y][x + 1] == oldChar:
        # RECURSIVE CASE
        ❺ floodFill(image, x + 1, y, newChar, oldChar)
    if x - 1 >= 0 and image[y][x - 1] == oldChar:
        # RECURSIVE CASE
        ❻ floodFill(image, x - 1, y, newChar, oldChar)
    ❼ return # BASE CASE

def printImage(image):
    for y in range(HEIGHT):
        # Print each row.
        for x in range(WIDTH):
            # Print each column.
            sys.stdout.write(image[y][x])
```