

```

        sys.stdout.write('\n')
    sys.stdout.write('\n')

printImage(im)
floodFill(im, 3, 3, 'o')
printImage(im)

```

The *floodfill.html* program contains the equivalent JavaScript code:

JavaScript

```

<script type="text/javascript">
// Create the image (make sure it's rectangular!)
❶ var im = ["..#####.....".split(""),
            "#.....#.....".split(""),
            "#.....#####.....".split(""),
            "#.....#.....#.....".split(""),
            "#.....#####.....".split(""),
            "#####.....#.....".split(""),
            ".....#.....#####.....".split(""),
            ".....####.....#####.....".split("")];

var HEIGHT = im.length;
var WIDTH = im[0].length;

function floodFill(image, x, y, newChar, oldChar) {
    if (oldChar === undefined) {
        // oldChar defaults to the character at x, y.
        ❷ oldChar = image[y][x];
    }
    if ((oldChar == newChar) || (image[y][x] != oldChar)) {
        // BASE CASE
        return;
    }

    image[y][x] = newChar; // Change the character.

    // Uncomment to view each step:
    //printImage(image);

    // Change the neighboring characters.
    if ((y + 1 < HEIGHT) && (image[y + 1][x] == oldChar)) {
        // RECURSIVE CASE
        ❸ floodFill(image, x, y + 1, newChar, oldChar);
    }
}

```