
```

def ackermann(m, n, indentation=None):
    if indentation is None:
        indentation = 0
    print('%sackermann(%s, %s)' % (' ' * indentation, m, n))

    if m == 0:
        # BASE CASE
        return n + 1
    elif m > 0 and n == 0:
        # RECURSIVE CASE
        return ackermann(m - 1, 1, indentation + 1)
    elif m > 0 and n > 0:
        # RECURSIVE CASE
        return ackermann(m - 1, ackermann(m, n - 1, indentat
ion + 1), indentation + 1)

print('Starting with m = 1, n = 1:')
print(ackermann(1, 1))
print('Starting with m = 2, n = 3:')
print(ackermann(2, 3))

```

And here is the equivalent *ackermann.html* JavaScript program:

```

<script type="text/javascript">
function ackermann(m, n, indentation) {
    if (indentation === undefined) {
        indentation = 0;
    }
    document.write(" ".repeat(indentation) + "ackermann(" +
m + ", " + n + ")\n");

    if (m === 0) {
        // BASE CASE
        return n + 1;
    } else if ((m > 0) && (n === 0)) {
        // RECURSIVE CASE
        return ackermann(m - 1, 1, indentation + 1);
    } else if ((m > 0) && (n > 0)) {
        // RECURSIVE CASE
        return ackermann(m - 1, ackermann(m, n - 1, indentat
ion + 1), indentation + 1);
    }
}

```