

Python

```
root = {'data': 'A', 'children': [{'data': 'B', 'children':
[{'data': 'D', 'children': []}]}, {'data': 'C', 'children':
[{'data': 'E', 'children': [{'data': 'G', 'children': []},
{'data': 'H', 'children': []}]}], {'data': 'F', 'children': []}]}}

def inorderTraverse(node):
    if len(node['children']) >= 1:
        # RECURSIVE CASE
        inorderTraverse(node['children'][0]) # Traverse the left child.
    print(node['data'], end=' ') # Access this node's data.
    if len(node['children']) >= 2:
        # RECURSIVE CASE
        inorderTraverse(node['children'][1]) # Traverse the right child.
    # BASE CASE
    return

inorderTraverse(root)
```

The *inorderTraversal.html* program contains the equivalent JavaScript code:

JavaScript

```
<script type="text/javascript">
root = {"data": "A", "children": [{"data": "B", "children":
[{"data": "D", "children": []}]}, {"data": "C", "children":
[{"data": "E", "children": [{"data": "G", "children": []},
{"data": "H", "children": []}]}], {"data": "F", "children": []}]}};

function inorderTraverse(node) {
    if (node["children"].length >= 1) {
        // RECURSIVE CASE
        inorderTraverse(node["children"][0]); // Traverse the left child.
    }
    document.write(node["data"] + " "); // Access this node's data.
    if (node["children"].length >= 2) {
        // RECURSIVE CASE
        inorderTraverse(node["children"][1]); // Traverse the right child.
    }
    // BASE CASE
    return;
}
```